

JL254A Datasheet



**SMART
SECURITY
SOLUTIONS**

Overview

Aruba 2930F Switch Series is designed for customer creating digital workplaces optimized for mobile users with an integrated wired and wireless approach. These basic Layer 3 access switches are easy to deploy and manage with advanced security and network management tools like Aruba ClearPass Policy Manager and Aruba AirWave and are ideal for enterprise edge, SMB and branch offices. A powerful Aruba ProVision ASIC delivers performance and value supporting the latest SDN applications with future proof programmability. The 2930F supports 10GbE uplinks, PoE+, robust QoS, RIP routing, Access OSPF, ACLs, Tunneled Node and IPv6. This JL254A has 48x 10/100/1000 access ports and 4x 1000/10G SFP+ transceiver slots for high speed connectivity.



Quick Spec

Table 1 shows the Quick Specs.

Product Code	JL254A
Type	Aruba 2930F 48G 4SFP+ Switch
I/O ports and slots	· 48 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T) Duplex: 10BASE-T/100BASE-TX: half or full 1000BASE-T: full only · 4 SFP+ 1/10GbE ports; PHY-less
Additional ports and slots	1 dual-personality (RJ-45 or USB micro-B) serial console port
Throughput	up to 112.0 Mp/s
Switching capacity	176 Gb/s
Dimensions	4.39 x 44.25 x 24.63 cm (1.73 x 17.42 x 9.7 in) 1U height

Specification

JL254A Specifications	
Type	Aruba 2930F 48G 4SFP+ Switch
System specifications	
I/O ports and slots	· 48 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T) Duplex: 10BASE-T/100BASE-TX: half or full 1000BASE-T: full only · 4 SFP+ 1/10GbE ports; PHY-less
Additional ports and slots	1 dual-personality (RJ-45 or USB micro-B) serial console port
Memory and processor	Dual Core ARM Cortex @ 1016 MHz, 1 GB DDR3 SDRAM Packet buffer size: 12.38 GB 4.5 MB Ingress/7.875MB Egress, 4 GB eMMC
Management	Aruba AirWave Network Management; IMC – Intelligent Management Center Command-line interface Web browser Configuration menu SNMP manager Telnet RMON1 FTP Out-of-band management (serial RS-232C or micro USB)



JL255A Datasheet



**SMART
SECURITY
SOLUTIONS**

Performance specifications	
1000 Mb Latency	< 3.8 μ s (64-byte packets)
10 Gbps Latency	< 1.6 μ s (64-byte packets)
Throughput	up to 112.0 Mp/s
Switching capacity	176 Gb/s
Routing table size	10000 entries (IPv4), 5000 entries (IPv6)
MAC address table size	32768 entries
Physical specifications	
Dimensions (W x D x H)	4.39 x 44.25 x 24.63 cm (1.73 x 17.42 x 9.7 in) 1U height
Electrical specifications	
80plus.org Certification	N/A
Description	N/A
Maximum heat dissipation	167.74 kJ/hr (159 BTU/hr)
Voltage	100 - 127 / 200 - 240 V ac, rated
Current	0.9/0.6 A
Maximum power rating	46.6 W
Idle power	32.7 W
Frequency	50/60 Hz
PoE power	N/A
Environmental specifications	
Operating temperature	0°C to 45°C (32°F to 113°F) up to 5000 Feet - 0C to 40C (32F to 104F) up to 10000 Feet
Operating relative humidity	15% to 95% @ 40°C (104°F) noncondensing
Nonoperating/Storage temperature	-40°C to 70°C (-40°F to 158°F) up to 15000 Feet
Nonoperating/Storage temperature	15% to 95% @65°C (149°F) noncondensing
Acoustic	Power: 49.7 dB, Pressure: 37.1 dB
Airflow direction	Side-to-side

Contact Us

Mobile : +213661211200 / +213661211201 / +213661211202 / +213661211203

Phone : +213 23 34 84 10 / +213 23 34 84 09

FAX : +213 23 34 84 69

Website: www.hactel.com / Email: info@hactel.com

Headquarters : Villa N° 79, lotissement D, Rue del Commune El Achour, Alger 16104

