

Switch (JL824A) Datasheet

HPE Networking Comware Switch48G PoE+ 4SFP+ EI 5140 (JL824A)



**SMART
SECURITY
SOLUTIONS**

Overview

The HPE Networking Comware Switch Series 5140 EI delivers scalability, high availability, and low TCO at the access layer of medium and large enterprise campus networks. The series offers enterprise-class QoS and security, HPE Intelligent Resilient Fabric (IRF) stacking, static layer 3 routing and RIP; convenient fixed 10GbE uplink ports, PoE+, ACLs, and IPv6; and delivers energy savings with Energy Efficient Ethernet.



Features

- Scalability and High Availability

The HPE Networking Comware Switch Series 5140 EI delivers scalability and enhances reliability of the network with HPE Intelligent Resilient Framework (IRF) technology. IRF stacking enables virtual resilient switching fabrics, where two or more switches perform as a single L2 switch and L3 router. HPE IRF stacking enhances performance and reliability with uninterrupted L2 switching and L3 forwarding and reduces operational complexity with simpler, flatter, and more agile networks. Four fixed uplinks (SFP, SFP+, and 10GBASE-T) deliver performance for bandwidth intensive applications. Link redundancy with support for protocols such as Spanning Tree/MSTP, RSTP, and Smart link provides high availability.

Comprehensive Security ControlFeatures

The HPE Networking Comware Switch Series 5140 EI supports flexible authentication methods including 802.1X and MAC Authentication for greater security and policy-driven application authentication. Per-user access control lists (ACLs) provide identity-driven security and access control. ACLs provide IP Layer 2 to Layer 4 traffic filtering while supporting global ACL, VLAN ACL, port ACL, and IPv6 ACL. Dynamic ARP protection with functions such as ARP Detection and ARP packet validation that block broadcasts from unauthorized hosts, preventing eavesdropping or theft of network data. Centralized security policy management and network protection with HPE Aruba Networking IMC End User Admission Domination (EAD) which integrates security policies, network access control, and access right control policies to form a cooperative security system. Enhance security with encryption of access methods (CLI, GUI, or MIB) through SSHv2, SSL, and/or SNMPv3, and other features including DHCP protection, IP source guard, and RADIUS/HWTACAS.

Simplified Management

The HPE Networking Comware Switch Series 5140 EI can be seamlessly managed with HPE Aruba Networking IMC to provide end-to-end network transparency with a consistent network experience through comprehensive configuration, compliance, and policy management. Supports SmartMC, an embedded network management tool with a web-based GUI to simplify operations and facilitate centralized management. It offers features such as configuration backup, software version management and seamless switch replacement. RMON and sFlow provide advanced monitoring and reporting capabilities for statistics, history, alarms, and events.

Enhanced Quality of Service

The HPE Networking Comware Switch Series 5140 EI supports advanced classifier-based QoS which groups traffic using multiple match criteria based on Layer 2 and 3 information; it applies QoS policies such as setting priority level and rate limit to selected traffic on a port, VLAN, or entire switch. Provides traffic prioritization with supported congestion actions include: strict priority (SP) queuing, weighted round robin (WRR), weighted random early detection (WRED), and SP+WRR and traffic policing with Committed Access Rate (CAR) and line rate. Reduce unwanted network traffic with broadcast control and limitation of broadcast traffic rate to cut down on unwanted network broadcast traffic.



Switch (JL824A) Datasheet

**HPE Networking Comware Switch48G
PoE+ 4SFP+ EI 5140 (JL824A)**



**SMART
SECURITY
SOLUTIONS**

Specification

Product Number	JL824A
Ports	48 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: Ports 1-48 support 10BASE-T/100BASE-TX, 1000BASE-T (full only); 4 SFP+ 1000/10000 SFP+ ports; 1 RJ-45 serial console port
Memory and processor	512 MB SDRAM, 256 MB flash
Latency	1000 Mb latency: < 5 μ s 10 Gbps latency: < 3 μ s
Throughput	131 Mpps
Switching capacity	176 Gbps
PoE capability	370W PoE+ Maximum, depending on model
Routing capabilities	Table Size: 1024 entries; MAC address: 16,384 entries IPv6 Ready Certified
Stacking capabilities	IRF 9 switches
Management features	HPE Aruba Networking IMC - Intelligent Management Center SmartMC Command-line interface Web browser SNMP manager
Power supply name	1 minimum power supply required (ordered separately)
Input voltage	AC Voltage: 100 VAC-240 VAC DC Voltage: -54 VDC to -57 VDC
Operating temperature	23°F to 113°F (-5°C to 45°C)
Power consumption	478W (Maximum), 47W (Idle)
Heat dissipation	Maximum: 160/1671 BTU/hr. (168.8/1762.91 kJ/hr.) for AC power. For DC power, minimum heat dissipation is 147 BTU/hr. and 3037 BTU/hr. maximum.
Product dimensions (metric)	4.36 x 44 x 40 cm
Weight	6 kg

Contact Us

Mobile : +213661211200 / +213661211201 / +213661211202 / +213661211203

Phone : +213 23 34 84 10 / +213 23 34 84 09

FAX : +213 23 34 84 69

Website: www.hactel.com / Email: info@hactel.com

Headquarters : Villa N° 79, lotissement D, Rue d'el Commune El Achour, Alger 16104

